Akulon® K224-HG6U BK223

NEXEO PLASTICS Material Code: 111431



GENERAL INFORMATION

Akulon[®] is our family of high performance polyamide 6 and polyamide 66 materials, used by customers across the world in applications ranging from automotive, electronics & electrical, to furniture and packaging.

We offer Akulon[®] grades for injection molding, blow molding and extrusion (including barrier film, stock shapes, convoluted tubes, and mono and multi filament).

In molded parts the material offers an excellent balance of easy design and processing with outstanding mechanical properties over a wide temperature range and in diverse conditions. Meanwhile for extrusion the strength, resilience and easy processing of Akulon[®] sets the market standards.

Application Example - Air Inlet Manifold



Akulon[®] PA6 is a thermoplastic with high heat resistance, making it ideal for applications such as air inlet manifolds. Akulon[®] PA6 allows for reliable solutions due to its stiffness and toughness, and better surface appearance leads to more costeffective solutions.

Physical and Chemical Properties

Appearance	Solid (pellets)
Color	Naturally opaque, dependent on the added pigment
Odor / pH	Not Available
Melting point/freezing point	220 to 230 °C
Flash Point °C	> 355 °C
Relative density	>1 (Water = 1)
Density	>1 g/cm ³
Solubility	Insoluble in cold water
Auto-ignition temperature	>420 °C
Decomposition temperature	>300 °C
Remarks:	If the color of the product is black, the product may contain up to 0.9% carbon black.

Nexeo Plastics 1780 Hughes Landing Blvd Suite 1000 The Woodlands, TX 77380 USA nexeoplastics.com To Place Your Order: US & Canada: 833.446.3936 getplastics@nexeoplastics.com Mexico: +52 55 4749 1710

ventas@nexeoplastics.com

US & Canada: 866.430.9666 Mexico: +52 81 1182 5109 techconnect@nexeoplastics.com

For Technical Questions:

Second Sustainable

All statements, information and data presented herein by Nexeo Plastics are believed to be accurate but are not to be taken as a guarantee or other representation for which Nexeo Plastics and its affiliates and subsidiaries assume legal responsibility.

NEXEO PLASTICS EXPRESSLY DISCLAIMS ANY AND ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARISING OUT OF ANY USE OF THE PRODUCTS OR SERVICES IDENTIFIED HEREIN OR RELIANCE ON ANY INFORMATION PROVIDED HEREIN.

End Markets

- Mobility
- Consumer Goods
- Electrical

Application Examples

- Air inlet manifolds
- Hot charged air ducts
- Structural reinforcements
- Engine covers
- Airbag containers
- Hydrogen pressure vessel
- Change air cooler caps
- Ski bindings
- Power tool housings
- Chainsaw housings
- Power equipment covers
- EV charging connectors
- Electrical connectors
- Miniature circuit breakers
- Residual current device
- Contactors

Brief Material Description

33% Glass Reinforced, Heat Stabilized, Black Nylon 6

Packaging / Minimum Order Quantity

- This is a made to order product
- Samples are available

SHOP AKULON® PROMOTABLE GRADES NOW!





All statements, information, recommendations and products must be thoroughly evaluated and verified by the end user to determine their applicability or suitability for each particular use. Typical values are indicative only and are not to be construed as being binding specifications.

* Trademark owned by a third party

©2023 Nexeo Plastics, LLC. All Rights Reserved.

