

Engine block heater for electric generators

Energy

Print Date: 2023-03-16

Benefits

- Engine heaters heat engine coolant to allow for easy engine start-up regardless of ambient temperature. The engine block heater is required to operate in continuous contact with coolant at temperatures between 35 and 50°C.



Details

Xytron™ offers long term high temperature resistance & hydrolysis resistance; Xytron™ is DSM's technical expertise and effective technical and commercial communication; Xytron™ also allows for easy processing;

Products

Xytron™ G4010T
PPS-GF40

Xytron™ G4024T
PPS-GF40

Speciality products

Xytron™

Akulon®, Arnite®, Arnitel®, EcoPaXX®, ForTii®, Novamid®, Stanyl®, UDea™ and Xytron™ are trademarks of DSM.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values. This document replaces all previous versions relating to this subject.

Copyright © DSM 2023. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of DSM.

