PAXON™ HDPE SP5504 Copolymer

NEXEO PLASTICS Material Code: 16136845

GENERAL INFORMATION

The unique development of ExxonMobil PAXON™ HDPE SP5504 processes similarly or better than conventional unimodal HDPE in blow molding applications.

When looking for a step change in performance or a step in the right direction – ExxonMobil PAXON™ HDPE SP5504 can deliver the improved processing and down gauge potential. This superior performance resin is available only from ExxonMobil.

Application Example



Exxonmobil PAXON™ HDPE SP5504 offers the ability to reduce product SKU's, leading to processing cost efficiencies when compared to competitive grades. ExxonMobil has completed test work in multiple applications including 10 liter F-Style bottles and oil bottles.

Physical and Chemical Properties	
Density	0.955 g/cm ³
Melt Index (190°C/2.16 kg)	0.35 g/10 min
Peak Melting Temperature	266°C
Vicat Softening Temperature	255 °C
Tensile Strength at Yield	4000 psi
Flexural Modulus - 1% Secant (1.3 mm/min)	1200 MPa mm/min
Environmental Stress-Crack Resistance	180 hr (100% lgepal)
Durometer Hardness (Shore D, 15 sec)	59
Charpy Notched Impact Strength	
-4 °F (-20 °C)	2.6 ft-lb/in ²
73 °F (23 °C)	3.9 ft-lb/in ²

Nexeo Plastics 1780 Hughes Landing Blvd Suite 1000 The Woodlands, TX 77380 USA nexeoplastics.com

To Place Your Order: US & Canada: 833.446.3936 getplastics@nexeoplastics.com

Mexico: +52 55 4749 1710 ventas@nexeoplastics.com All statements, information and data presented herein by Nexeo Plastics are believed to be accurate but are not to be taken as

a guarantee or other representation for which Nexeo Plastics and its affiliates and subsidiaries assume legal responsibility

OF THE PRODUCTS OR SERVICES IDENTIFIED HEREIN OR RELIANCE ON ANY INFORMATION PROVIDED HEREIN.

NEXEO PLASTICS EXPRESSLY DISCLAIMS ANY AND ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARISING OUT OF ANY USE

For Technical Questions: US & Canada: 866.430.9666 Mexico: +52 81 1182 5109 techconnect@nexeoplastics.com



PROMOTABLE GRADE!



End Markets

- Consumer Goods
- Healthcare
- Industrial and Electrical
- Packaging

Application Examples

- **Blow Molding**
- Food Packaging
- Personal Care
- **Sheet Extrusion**

Brief Material Description

This HDPE copolymer has remarkable stiffness allowing lightweighting possibilities. It enhances products without compromising strength.

Availability

Samples are available upon request.





All statements, information, recommendations and products must be thoroughly evaluated and verified by the end user to determine their applicability or suitability for each particular use. Typical values are indicative only and are not to be construed as being binding specifications.

* Trademark owned by a third party

©2023 Nexeo Plastics, LLC. All Rights Reserved.